Appendix F

Water Resources



WATERS REPORT INDIANA DEPARTMENT OF TRANSPORTATION (INDOT) STATE ROUTE 234 IN MONTGOMERY COUNTY, INDIANA SMALL STRUCTURE REPLACEMENT

DES. NO.: 1800155 ASSET ID #: CV 234-054-46.50

Prepared by: Mathew Aldridge Mathew.Aldridge@burgessniple.com 614-459-7272 ext. 1022 Burgess & Niple Inc.

Completed Date: 4/6/2020

Date of Field Reconnaissance: 10/16/2019

Location:

Section 16, Township 17N, Range 3W Ladoga, Indiana Quadrangle Montgomery County, Indiana HUC 12: 0512 0108 1206 (Little Raccoon Creek-Big Raccoon Creek) 39.915737, -86.752866

1.0 PROJECT DESCRIPTION

The proposed project is located 6.55 miles west of State Route (SR) 75 in Montgomery County, Indiana. The existing structures are triple 24 in. diameter corrugated metal pipes that are 30 ft. in length on a 30° skew. The proposed project will be to replace the structures with a 6 ft. by 3 ft. reinforced concrete box.

2.0 DESKTOP RECONNAISSANCE

The literature review for this report included review of proposed project plans, U.S. Geological Survey (USGS) topographic maps, current aerial photography, National Hydrography Database (NHD), National Wetlands Inventory (NWI) maps, soils maps and soil survey information, Federal Emergency Management Agency (FEMA) flood hazard mapping, and Indiana Department of Environmental Management (IDEM) water quality and use designation information, as applicable. Findings of the literature review are summarized below.

2.1 USGS Topographic Mapping and Aerial Photography

The project location is depicted on the Ladoga, Indiana 7.5-Minute Series USGS topographic quadrangle. Aerial photography was evaluated from imagery obtained from Indiana Map (https://maps.indiana.edu).

The study area is approximately 0.517 acres located in a rural setting along State Route (SR) 234 and approximately 2.5 miles east of Ladoga. There are no streams located within the project area depicted on the USGS topographic map. The elevation of the surrounding area is approximately 890 ft. above mean sea level (AMSL). Aerial photography shows the entirety of the area surrounding the study area as active farmland. NHD shows one stream flowing from north to south through the study area.

2.2 Soils

According to the Soil Survey Geographic (SSURGO) Database for Montgomery County, Indiana, the study area does contain soil areas with nationally listed hydric soils.

Two soil units are mapped within the study area. Crosby silt loam, fine loamy subsoil, 0 to 2 percent slopes (CwA) and Treaty silty clay loam, 0 to 1 percent slopes. Both are rated as hydric soils.

Review results for soil mapping and unit descriptions obtained from the NRCS Web Soil Survey (http://websoilsurvey.nrcs.usda.gov) are summarized in **Table 1** below.

Table 1 Soil Survey

Soil Name	Map Abbreviation	Hydric Range
Crosby silt loam, fine loamy subsoil, 0 to 2 percent slopes	CwA	1-32%
Treaty silty clay loam, 0 to 1 percent slopes	Ту	66-99%

2.3 National Wetland Inventory (NWI) Information

No stream, wetlands, ponds or other mapped NWI features are depicted in the study area.

One NWI mapped riverine feature is located adjacent to the south of the study area (R4SBC).

NWI map review results obtained from the U.S. Fish & Wildlife Service's Wetlands Mapper application (https://www.fws.gov/wetlands/Data/Mapper.html), are summarized in **Table 2** below.

Table 2 NWI Mapped Features

Abbreviation	Classification	Description	Location
R4SBC	Riverine/Intermittent/	Stream	Adjacent to the South of
K45DC	Streambed/Seasonally Flooded	Stream	Study Area

2.4 Flood Hazard Mapping

The project location appears on Flood Insurance Rate Map (FIRM) panel 18107C0270C (effective 2/2/2012). It is shown located entirely within Zone X, indicating that it is in an Area of Minimal Flood Hazard.

3.0 FIELD RECONNAISSANCE

The study area was visited by Mathew Aldridge & Matthew Kestner, Environmental Scientists of B&N on October 16, 2019 to observe and document existing conditions, and to identify and evaluate potentially jurisdictional "waters of the U.S." (WOTUS) and other aquatic resources Weather conditions were a high of 62°F and 0.03 inches of precipitation had been recorded in the previous 72 hours. Findings of the field investigation are summarized below.

3.1 Streams

No stream was observed in the study area.

3.2 Wetlands

One data collection point was established in the study area to characterize and delineate potential wetland resources, and adjacent upland communities. Vegetation, hydrology, and soil data were collected at each sample point in accordance with applicable U.S. Army Corps of Engineers (USACE) Regional Supplement delineation protocols (*Midwest Regional Supplement*). Data collection results for each sample plot are discussed below:

Soil Point (SP) 1: SP-1 was taken at the culvert ingress north of SR 234. This soil exhibited hydric soil indicators, Depleted Matrix and Redox Depressions with a 10YR 4/1 matrix and 7.5 YR 4/6 redox features. A restrictive layer of hardpan was discovered 16 inches below ground surface. This point had a dominance of *Carex grayi* and *Setaria faberi*. Hydrophytic vegetation was neither dominant nor prevalent. This point exhibited geomorphic position, drainage patterns, and surface soil cracks, all of which are secondary wetland hydrology indicators. While wetland hydrology and hydric soils were present, this point did not pass wetland vegetation criteria to be classified as a wetland.

Wetland and Data Point characteristics are summarized in **Table 4**.

Table 4
Data Point Summary Table

Data Point	Vegetation	Soils	Hydrology	Wetland
SP 1	No	Yes	Yes	No

3.3 Open Waters

No ponds, lakes, or other open water features were observed in the study area.

3.4 Other Features

No roadside ditches or other linear water features were observed in the study area.

4.0 CONCLUSION

Based on the findings of this investigation, B&N concludes that there are no potentially jurisdictional streams or wetlands located within the study area. No ponds, lakes, ditches or other water features were observed in the study area.

These waterways are likely Waters of the U.S. Every effort should be taken to avoid and minimize impacts to the waterway and wetlands. If impacts are necessary, then mitigation may be required. The INDOT Environmental Services Division should be contacted immediately if impacts will occur. The final determination of jurisdictional waters is ultimately made by the U.S. Army Corps of Engineers. This report is our best judgement based on the guidelines set forth by the Corps.

5.0 ACKNOWLEDGEMENT

The waters determination has been prepared based on the best available information interpreted in the light of the investigator's training, experience, and professional judgement in conformance with the 1987 Corps of Engineers Wetlands Delineation Manual, the appropriate regional supplement, the USACE Jurisdictional Determination Form Instructional Guidebook, and other appropriate agency guidelines

Respectfully,

Mathew Aldridge

4/6/202


Environmental Scientist

Burgess & Niple, Inc. / Crawfordsville District

ATTACHMENTS

Project Location Map Attachment 1 USGS Topographic Map **Attachment 2** Attachment 3 Aerial Map National Hydrography Dataset (NHD) Map **Attachment 4** NRCS Hydric Soil Map **Attachment 5 Attachment 6 NWI Features Map** Attachment 7 FEMA Flood Hazard Map Delineation Map **Attachment 8** Attachment 9 Photo Orientation Map & Site Photographs Water Resources Data Forms Attachment 10 Highlighted attachments removed to avoid duplication within the CE. Refer to

Appendix B for excluded Attachments.



0 125 250 500 Feet

Attachment 4

SR 234 - Culvert Replacement

Indiana Dept. of Transportation (INDOT)

Sources:

Non Orthophotography

<u>Data</u> - Obtained from the State of Indiana Geographical Information Office Library

Information Office Library

<u>Orthophotography</u> - Obtained from Indiana Map Framework Data (www.indianamap.org)


Prepared By: Burgess & Niple

Map Projection: UTM Zone 16 N Map Datum: NAD83

NHD Map

Des. No.: 1800155

Montgomery County





Attachment 5

SR 234 - Culvert Replacement

Sources:

Non Orthophotography

<u>Data</u> - Obtained from the State of Indiana Geographical Information Office Library

<u>Orthophotography</u> - Obtained from Indiana Map Framework Data (www.indianamap.org)

(www.iiiuiananap.org

Map Projection: UTM Zone 16 N Map Datum: NAD83

Prepared By: Burgess & Niple

NRCS Hydric Soil Map


Indiana Dept. of Transportation (INDOT)

October 2019

Des. No.: 1800155

Montgomery County





Attachment 6

Sources:

Non Orthophotography

<u>Data</u> - Obtained from the State of Indiana Geographical Information Office Library


<u>Orthophotography</u> - Obtained from Indiana Map Framework Data (www.indianamap.org)

Map Projection: UTM Zone 16 N Map Datum: NAD83

Prepared By: Burgess & Niple

Indiana Dept. of Transportation (INDOT) S.R. 234 - Culvert Replacement Des. No.: 1800155 Montgomery County

NWI Map



500 1,000 2,000 Feet

Attachment 7

Indiana Dept. of Transportation (INDOT) SR 234 - Culvert Replacement Sources: Des. No : 1800155

Montgomery County

FEMA Flood Hazard Map


Non Orthophotography


Data - Obtained from the State of Indiana Geographical Information Office Library

Orthophotography - Obtained from Indiana Map Framework Data (www.indianamap.org)

Map Projection: UTM Zone 16 N Map Datum: NAD83

Prepared By: Burgess & Niple





Attachment 9

Indiana Dept. of Transportation (INDOT) SR 234 - Culvert Replacement Des. No.: 1800155 Montgomery County

J , ,

Sources:

Non Orthophotography

<u>Data</u> - Obtained from the State of Indiana Geographical Information Office Library

<u>Orthophotography</u> - Obtained from Indiana Map Framework Data (www.indianamap.org)

Map Projection: UTM Zone 16 N Map Datum: NAD83

Prepared By: Burgess & Niple

Delineation Map

WETLAND DETERMINATION DATA FORM - Midwest Region

Project/Site: Des. No.: 1800155 - SR 234		City/Cour	nty: Montgo	mery County	Sampling Date:	10/16/2019
Applicant/Owner: Indiana Department of Transporta	tion (INDOT	ſ) <u> </u>		State: IN	Sampling Point:	SP 1
Investigator(s): M. Aldridge & M. Kestner		Section, T	ownship, Ra	ange: S16/T17N/R3W		
Landform (hillside, terrace, etc.): Roadside Depression		ι	_ocal relief (d	concave, convex, none):	Concave	
Slope (%): 0-2 Lat: 39.915793		Long: _{	86.752798		Datum: NAD 83	
Soil Map Unit Name: Crosby silt loam, fine loamy subsc	oil (CwA)			NWI classit	ication: N/A	
Are climatic / hydrologic conditions on the site typical fo		of year?	Yes X	No (If no, exp	olain in Remarks.)	
Are Vegetation X , Soil , or Hydrology X s	ignificantly o				Yes X No	
Are Vegetation, Soil, or Hydrologyn						
SUMMARY OF FINDINGS – Attach site ma						tures, etc.
Hydrophytic Vegetation Present? Yes No	Х	Is the	Sampled A	rea		
		withir	n a Wetland	? Yes	No <u>X</u>	
Wetland Hydrology Present? Yes X No						
Remarks: Soil Point (SP) 1 was taken to the north of SR 234 with		sion adjacent	to the culver	rt.		
VEGETATION – Use scientific names of plan	nts. Absolute	Dominant	Indicator	г		
<u>Tree Stratum</u> (Plot size: 30 ft.)	Absolute % Cover	Dominant Species?	Indicator Status	Dominance Test wo	ksheet:	
1				Number of Dominant Are OBL, FACW, or F	•	1 (A)
3.				Total Number of Dom Across All Strata:	inant Species	2 (B)
4 5.				Percent of Dominant		(5)
Sapling/Shrub Stratum (Plot size: 15 ft.)	:	=Total Cover		Are OBL, FACW, or F	•	.0% (A/B)
1				Prevalence Index wo	orksheet:	
2.				Total % Cover of	: Multiply	by:
3.				OBL species 0	x 1 =	0
4				FACW species 5		00
5				FACILITIES C		0
Herb Stratum (Plot size: 5 ft.)		=Total Cover		FACU species 6: UPL species 0		<u>60</u> 0
1. Carex grayi	50	Yes	FACW	Column Totals: 11		60 (B)
Setaria faberi	50	Yes	FACU	Prevalence Index	``	(5)
3. Glechoma hederacea	10	No	FACU	11000.0.0		
4. Digitaria sanguinalis	5	No	FACU	Hydrophytic Vegetat	ion Indicators:	
5.				1 - Rapid Test for	Hydrophytic Vegeta	ation
6.				2 - Dominance Te	est is >50%	
7				3 - Prevalence Inc		
8				· —	Adaptations ¹ (Provi	
9.					s or on a separate	'
10					ophytic Vegetation ¹	, , ,
Woody Vine Stratum (Plot size: 5 ft.)		=Total Cover		¹ Indicators of hydric s be present, unless dis	•	
1				Hydrophytic		
2		7 / 10		Vegetation	N. V	
		=Total Cover		Present? Yes	No <u>X</u>	-
Remarks: (Include photo numbers here or on a separa Vegetation is regularly mowed	ate sheet.)					

SOIL Sampling Point: SP 1

Profile Des	cription: (Describe	to the depth	needed to doo	ument th	ne indica	tor or	confirm the a	bsence o	f indicators	s.)	
Depth	Matrix		Redo	x Feature	es						
(inches)	Color (moist)	%	Color (moist)	%	Type ¹	Loc ²	Textu	re		Remarks	
0-16	10YR 4/1	90	7.5YR 4/6	10		M	Loamy/C	lavev	Promine	nt redox conce	entrations
	· 			· —			-				
	·						-				
<u> </u>											
1 _{Type: C=C}	oncentration, D=Dep	letion PM-P	educed Matrix	MS-Masi	ed Sano		. 2	l ocation:	DI -Doro I	ining, M=Matri	
Hydric Soil		iction, rtivi–rt	caacca matrix,	IVIO-IVIASI	cca Garic	Oranis				matic Hydric	•
Histosol			Sandy Gle	eved Mati	ix (S4)		•		Prairie Red	_	oons .
	pipedon (A2)		Sandy Re		IX (O+)		_			Masses (F12)	
	istic (A3)		Stripped M		:)		_		arent Mater		
	en Sulfide (A4)		Dark Surf		')		_			κ Surface (F22)\
	d Layers (A5)		Loamy Mu		eral (F1)		-		(Explain in F		-)
	uck (A10)		Loamy GI				-		(Explain in I	tomantoj	
	d Below Dark Surface	e (A11)	X Depleted	-	, ,						
l — ·	ark Surface (A12)	. ()	Redox Da	•			3	Indicators	of hydrophy	ytic vegetation	and
	/Jucky Mineral (S1)		Depleted							must be pres	
	ucky Peat or Peat (S3	3)	X Redox De							or problematic.	
	Layer (if observed):			<u> </u>	,	ĺ					
Type:	Hardpa	0									
Depth (i	·	16	_				Hydric Soil	Present	>	Yes X	No
- ' `		10	_				1190110 0011	T reseme	•	100 <u>X</u>	
Remarks:											
HYDROLO	ngv										
r											
1	drology Indicators:										
	cators (minimum of c	ne is require			(5.0)					(minimum of t	wo required)
	Water (A1)		Water-Sta				_		ce Soil Cracl	, ,	
	ater Table (A2)		Aquatic F	•	•		-	_	age Patterns	• •	
Saturati			True Aqua				_			r Table (C2)	
	Marks (B1)		Hydrogen						sh Burrows	on Aerial Ima	(CO)
	nt Deposits (B2) posits (B3)		Oxidized I Presence	•		_	-			ed Plants (D1)	, ,
l ——	at or Crust (B4)		Recent Iro				_ le (C6)		orphic Posit		
	posits (B5)		Thin Muck			ileu ooi	_		Neutral Test	` ,	
·	on Visible on Aerial I	magery (B7)	Gauge or		, ,		-		veutiai rest	(D3)	
	y Vegetated Concave										
Field Obse	, <u> </u>	- Carraco (Do)		piani iii i	omano,						
	ter Present? Ye	c	No X	Depth (in	oches).						
Water Table			No X	Depth (ii							
Saturation F			No X	Depth (ii	_		Wetland	Hydrolog	y Present?	Yes X	No
	pillary fringe)	~	<u> </u>	Dopur (ii			Victiana	nyarolog	y i resent.	103 <u>X</u>	
	ecorded Data (stream	gauge, moni	toring well, aeria	al photos	previous	s inspec	ctions). if avail	able:			
	2 2 2 2 2 3 3 4 3 3 3 3 3 3 3 3 3 3 3 3	J			,		,, a.a.				
Remarks:											
Hydrology d	isturbed by the culver	t and impour	ndment caused	by the roa	adway						

US Army Corps of Engineers Midwest Region – Version 2.0

Appendix G

Public Involvement

Notice of Survey

Date: 7/18/2019

SUBJECT: SR 234 Small Structure Replacement
DES No. 1800155, Montgomery County, Indiana

Dear Property Owner:

CECon, on behalf of Infrastructure Engineering, Inc., will perform a survey for the replacement of the SR 234 Small Structure over Unnamed Tributary to Little Raccoon Creek, Montgomery County, Indiana. This work is associated with Indiana Department of Transportation (INDOT) Des No. 1800155. Our information indicates that you own or occupy property near the above referenced project. Our employees will be performing a survey of the project area in the near future. It may be necessary for them to come onto your property to complete this work. This is permitted by law per Indiana Code IC 8-23-7-26. They will show you their identification, if you are available, before coming onto your property. If you have sold this property, or it is occupied by someone else, please let us know the name and address of the new owner or current occupant so we can contact them about the survey.

At this stage, we generally do not know what effect, if any, our project may eventually have on your property. If we determine later that your property is involved, you will be contacted with additional information.

The survey work will include mapping the location of features such as trees, buildings, fences and drives, and obtaining ground elevations. The survey is needed for the proper planning and design of this project. Please be assured of our sincere desire to cause you as little inconvenience as possible during this survey. If any problems do occur, please contact our field crew or contact me at the telephone number or address shown above for our office. The Infrastructure Engineering, Inc. Project Manager is also available for questions concerning this project. His contact information is as follows:

Nick Bergman, PE 201 South Capitol Avenue, Suite 490 Indianapolis, IN 46225 (317) 243-9800

Kurt M. Vorderheide

Sincerely.

Kurt M. Vonderheide, PS Senior Survey Project Manager

Owner Name	Owner Address	City, State and Zip Code
BradleyFarms Inc II	6161 E. SR 234	Ladoga, IN 47954-7204
Ellen Louise Smullen GST Exempt Trust c/o Soy Capital Bank & Trust Co ATTN: Farm Department	455 N. Main St.	Decatur, IL 62523-1180

Appendix H

Air Quality

tructure 7.28 mi W of SR 75		Crawfordsville	0 STBG	\$411,752.00 Bridge ROW	3ridge ROW	RW	\$3,200.00	\$800.00		\$2
ment										
tructure 6.55 mi W of SR 75		Crawfordsville	O <mark>STBG</mark>	\$377,041.00 Bridge ROW	Bridge ROW	RW	\$6,400.00	\$1,600.00		\$
Painting 5.77 mi N o	5.77 mi N of I-74, over CSX RR	Crawfordsville	0 STBG	\$297,783.00 Bridge Constr	Bridge Construction	CN	\$238,226.40	\$59,556.60		
					Bridge Consulting	PE	\$16,000.00	\$4,000.00	\$20,000.00	
\$297,783, No MPO										
Painting 0.32 mi N of Sugar Creek	US 136, over	Crawfordsville	0 STBG	\$1,191,133.00 Bridge Constr	Bridge Construction	CN	\$952,906.40	\$238,226.60		
				В	Bridge Consulting	PE	\$96,000.00	\$24,000.00	\$120,000.00	
,191,133. No MPO										
hin Deck 3.38 mi E o	3.38 mi E of SR 47, over I-74 (EB/WB	Crawfordsville	0 STBG	\$269,080.00 Bridge Constru	Bridge Construction	CN	\$215,264.00	\$53,816.00		
				E	Bridge Consulting	PE	\$16,000.00	\$4,000.00	\$20,000.00	
9,080. No MPO										
hin Deck 3.17 mi S o	3.17 mi S of SR 32, over Offield Creek	Crawfordsville	0 STBG	\$176,066,00 Bridge Constr	Bridge Construction	CN	\$124,852.80	\$31,213.20		
				Е	Bridge Consulting	PE	\$16,000.00	\$4,000.00	\$20,000.00	
6,066. No MPO										
t. Improv. W/ 0.93 mi S of US urn Lanes Dr. intersection	⊱136, Durham	Crawfordsville	0 STBG	\$688,643.00	\$688,643.00 Safety Consulting	PE	\$52,000.00	\$13,000.00		\$65
t. Improv. W/ 0.93 mi S or urn Lanes Dr. intersec	0.93 mi S of US-136, Durham (Dr. intersection	Crawfordsville	0 STBG	\$853,643.00 Safety	Safety ROW	RW	\$80,000.00	\$20,000.00		\$100
Maintenance 4.52 mi E or pair Creek	4.52 mi E of I-74, over Muskrat (Creek	Crawfordsville	0 STBG	\$119,227.00 E	\$119,227.00 Bridge Consulting	PE	\$12,000.00	\$3,000.00	\$15,000.00	
				- E	Bridge Construction	CN	\$83,381.60	\$20,845.40		\$102

Appendix I

Additional Studies

Lar	nd and Water Conservati	ion Fund (LWCF)	County Property List for Indiana (Last Updated July 2020)
ProjectNumber	SubProjectCode	County	Property
1800133	1800133	Montgomery	Lincoln Activity Area (Lincoln Recreation Center)
1800161	1800161E	Montgomery	Shades State Park
1800171	1800171L	Montgomery	Shades State Park
1800211	1800211	Montgomery	Lake Waveland Park
1800308	1800308	Montgomery	Shades State Park
1800312	1800312N	Montgomery	Shades State Park
1800327	18003271	Montgomery	Shades State Park
1800363	1800363BB	Montgomery	Shades State Park
1800405	1800405A	Montgomery	Calvert and Porter Woods
1800413	1800413R	Montgomery	Shades State Park
1800456	1800456	Montgomery	Shades State Park
1800480	1800480	Montgomery	Darlington Old School Park

^{*}Park names may have changed. If acquisition of publically owned land or impacts to publically owned land is anticipated, coordination with IDNR, Division of Outdoor Recreation, should occur.

Calculations

Montgomery County Percent Population Below Poverty Level

Income in the past 12 months below poverty level: 3,693

Total Population: 36,581

3,693/36,581 **= 10.09**%

Census Tract 9575 Percent Population Below Poverty Level

Income in the past 12 months below poverty level: 438

Total Population: 3,616

438/ 3,616 = **12.11**%

125% of COC: $10.09\% \times 125\% = 12.61\%$

12.11% < 12.61%

Montgomery County Percent Minority Population

Total Population White Alone: 37,430

Total Population: 38,276

38,276- 37,430 = **846** 846 / 38,276 = **2.21**%

Census Tract 9575 Percent Minority Population

Total Population White Alone: 3,619

Total Population: 3,638


3,638 - 3,619 = **19** 19 / 3,638 = **0.52**%

125% of COC: $2.21\% \times 125\% = 2.76\%$

0.52% < 2.76%



This document was created by an application that isn't licensed to use <u>novaPDF</u>. Purchase a license to generate PDF files without this notice.



This document was created by an application that isn't licensed to use <u>novaPDF</u>. Purchase a license to generate PDF files without this notice.



Indiana Floodplain Information Portal Report

Point of Interest

Effective Flood Zone:

Χ

Preliminary Flood Zone:

N/A

Best Available Flood Zone:

Χ

Approximate Flood Elevation:

863ft NAVD88

Source:

Zone A Model Delineation

Nearest Stream:

LITTLE RACCOON CREEK

Map Legend

Point of Interest



Nearest Point on Stream

Best Available Flood Zone

FEMA Zone AE Floodway

DNR Detailed Floodway

DNR Approximate Floodway

FEMA Zone A

FEMA Zone AE

DNR Detailed Fringe

DNR Approximate Fringe


🔃 Additional Floodplain Area

FEMA Protected by Levee

FEMA Floodplain - Ponding (Depth)

FEMA Floodplain - Sheet Flow (Depth)

Site Map with Best Available Flood Zone



Approximate scale 1:12,000

Abbreviated Engineer's Report

SR 234 over UNT to Little Raccoon Creek Small Structure Project

CV 234-054-46.50 Des. No. 1800155

April 2020

Prepared For Indiana Department of Transportation



TABLE OF CONTENTS

Purpose of Report	1
Project Location	1
Project Purpose and Need	1
Existing Facility	1
Traffic Data	2
Crash Data	2
Alternatives	3
Maintenance of Traffic Concept	4
Environmental Impacts	4
Permits Required	5
Right-of-Way Impacts	5
Railroad Impacts	5
Utility Impacts	5
Survey Requirements	5
Initial Field Check Meeting	5
Preliminary Cost Estimate	6
Phase Costs for CN/PE/RR/RW/UT	6
Concurrence	7
Appendix A - Location Map	A-1
Appendix B – Site Photographs	B-1
Appendix C – Culvert Inspection Report	C-1
Appendix D – Traffic Data	D-1
Appendix E – INDOT Hydraulics Approval Letters	E-1
Appendix F – Typical Sections	F-1
Appendix G – Quantity Calculations and Cost Estimate	G-1
Appendix H – Initial Field Check Meeting	
Appendix I – 811 Design Ticket	
Appendix J – Mini Scope	
Appendix K – Red Flag Investigation	
1 (44)	

Highlighted appendix removed to reduce size.

PURPOSE OF REPORT

The purpose of this report is to document the engineering assessment phase of project development, including all coordination that has been completed in preparation for this small structure replacement project. This document outlines the proposal and is intended to serve as a guide for subsequent survey, design, environmental, right of way and other project activities leading to construction. The preferred alternative identified in this document is considered pre-decisional, pending the outcome of environmental studies.

PROJECT LOCATION

This project is located on SR 234, 6.55 miles west of SR 75 at reference post 46+50 in Montgomery County within the Indiana Department of Transportation's (INDOT) Crawfordsville District, Crawfordsville Sub-District. The GPS coordinates at the project are 39° 54′ 56.6″ North and 86° 45′ 11.0″ West. The project is located within Section 16 of Township 17 North, Range 3 West in the Ladoga Quadrangle Map. The project is not in a Regional Planning Organization. The project location map is in Appendix A.

PROJECT PURPOSE AND NEED

The existing small structure is exhibiting severe signs of deterioration with a potential for localized failures. The structure does not meet current design standards and is hydraulically undersized to handle the design flow. Therefore, the project need is to address the deteriorated condition of the existing substandard small structure.

The project purpose is to improve the safety, condition, and performance of this crossing.

EXISTING FACILITY

ROADWAY

The existing roadway facility is classified as a major collector. The roadway is not part of the US National Highway System (NHS) nor the National Truck Network. The posted speed limit at the project location is 55 mph. Table 1 shows the roadway information for SR 234.

The existing roadway typical section has two 11.5-foot lanes and 2-foot usable shoulder with no paved shoulders. The side slope from the edge of pavement on either side of the culvert consists of an approximate 4(H):1(V) to 6(H):1(V) slope to the roadside ditch.

Geometric Criteria					
Design Speed	55 MPH	Functional Class	Major Collector		
Design Criteria	3R, Non-Freeway	Rural/Urban	Rural		
Terrain	Level	Access Control	None		
	Approach C	ross Section			
IDM Figure Reference	IDM 55-3B				
Travel Lane Count	2	Travel Lane Width	11.5' (Existing) 11' (Minimum Req'd.)		
Shoulder Width (Usable)	2' (Existing) 3' (Minimum Req'd.)	Shoulder Width (paved)	0' (Existing) 2' (Minimum Req'd.)		
Mainline Pavement	НМА	Shoulder Pavement	Aggregate (Existing)		
	Align	ment			
Horizontal	Tangent	Vertical	Sag Curve		

Table 1: Roadway Information for SR 234

VERTICAL ALIGNMENT

Based on the survey data for this project, the existing sag vertical curve has an approximate incoming grade of -0.90%, an outgoing grade of +1.33%, and a 300-foot curve length. The required curve length for a curve with these grades and speeds is 260 feet, which appears to be met. No design exception is required to retain the existing vertical alignment.

SMALL STRUCTURE

The existing culvert, CV 234-054-46.50, carries SR 234 over an Unnamed Tributary (UNT) to Little Raccoon Creek, which flows generally from northeast to southwest. The existing structure consists of triple 24-inch diameter corrugated metal pipes with a length of 30 feet at a skew of 30° to the roadway. The existing culvert has approximately 2 feet cover. The maximum horizontal opening between the three 24-inch barrels is 8 feet with a maximum vertical opening of 2 feet. The headwall exists at both ends of structure and has spalling with exposed rebar at both ends. The year built is unknown and there are no known rehabilitations to the structure. See Appendix B for site photographs of the small structure.

The small structure was last inspected on May 10, 2019. According to the 2019 Culvert Inspection Report, the culvert has a condition rating of 4 (poor) and is recommended for replacement. There is heavy rusting throughout the structure from the spring line to the invert with portions of invert failure. The headwalls have heavy spalling with exposed rebar at both ends of the structure. The culvert has a channel protection rating of 8 (good). The structure does not have a clearly defined channel on the upstream side and the downstream channel is a farmed swale. The culvert inspection frequency is 12 months. See Appendix C for the 2019 Culvert Inspection Report.

TRAFFIC DATA

Per the Traffic Count Database System (TCDS), INDOT conducted traffic counts approximately 1.1 miles west of the project in May of 2018. INDOT provided traffic forecast information for build year. A growth rate of 0.72% was used to forecast the traffic. Table 2 shows the annual daily traffic (ADT) for the count year (2018), current year (2020), build year (2022), and the design year (2042).

Year	ADT
2018 – Count Year	1,775
2020 – Current Year	1,800
2022 – Build Year	1,826
2042 – Design Year	2,109

Table 2: Traffic Data

From the INDOT traffic forecast report, the design hourly volume (DHV) is 8.73%, the directional split is 49.97%, and the percentage of trucks is 9.01%. The traffic data from the traffic forecast report can be found in Appendix D.

CRASH DATA

Crash data from 2017 to 2020 was analyzed within a half mile of the project location. three crashes were identified in the area. Table 3 shows the location, manner of collision, severity level: fatality, injury, or property damage only (PDO), and any other contributing factors.

Table 3: Crash History

Year	Approximate Location	Manner of Collision	Severity Level	Other Contributing Factors
2018	SR 234E & CR750E	Insecure Load	PDO	Daytime
2018	SR 234E & CR825E	Collision with deer	PDO	Daytime
2019	SR 234E & CR750E	Collision with deer	PDO	Dark (Not Lighted)

The first incident occurred at or near the intersection of SR 234 E and CR 750 E due to an insecure load of gravel on the front vehicle's trailer. Gravel fell from the front vehicle trailer causing damage on rear vehicle. Only minor paint and windshield chipping occurred.

The second collision within the area was with deer during the daytime with clear weather and dry pavement and the third collision was with deer during the night with dry pavement.

Based on the above information, the reported incidents do not appear to be due to the culvert, lack of sight distance provided by the roadway, nor narrow shoulders.

ALTERNATIVES

Per the INDOT provided Hydraulic Design Memorandum dated March 20, 2020, there are two approved options. The first approved option consists of installing a Cured-in-Place-Pipe liner through the existing barrels and adding a Class I Riprap apron for scour protection. The second option includes replacing the existing structure with a 6 ft span by 3 ft rise reinforced concrete box (RCB) sumped 18 inches. The RCB option requires a Class 1 riprap apron at the outlet and a revetment riprap apron at the inlet to protect the structure from scour. See Appendix E for the INDOT Hydraulic Design Memorandum.

It was expressed during the initial field check meeting that the reinforced concrete box without guardrail is preferred, but its selection is contingent on if the construction costs are within the current budget and if the life-cycle analysis shows it to be the most cost-effective solution.

The existing headwall is within the clear zone and represents a safety hazard for vehicles departing the roadway. Due to the safety concerns and the short length of the hazard, providing increased safety through the project area was evaluated as part of this assessment. Extending the length of the replacement culvert to eliminate the need for a headwall and guardrail protection was evaluated.

ALTERNATE NO. 1 – 6' (SPAN) X 3' (RISE) RCB (NO GUARDRAIL)

This alternate uses an 84 feet long 6-foot (span) by 3-foot (rise) reinforced concrete box structure sumped 18 inches. A Class 1 riprap apron at the outlet and a revetment riprap apron at the inlet to protect the structure from scour.

The roadway typical section will remain as existing through the project limits with 2-11.5-foot lanes and a 2' usable shoulder. A Level 1 Design Exception required for the shoulder width. The structure will be of sufficient length to have the end of the structure be outside of the clear zone and eliminate the need for protection. The side slopes are proposed to be graded at 4(H):1(V) to tie back into existing ground or ditch. Refer to the Typical Sections in Appendix F.

The traversable sideslope is required to be maintained at least the guardrail runout length of 185 ft in front of the structure. Therefore, the project limits will need to be approximately 188 feet on either side of the centerline of the structure (376' total). However, only approximately 20' of this will be full depth pavement replacement. The remainder of the project limits will be limited to HMA overlay and slope grading. The existing vertical profile provides adequate cover over the structure.

ALTERNATE NO. 2 – 6' (SPAN) X 3' (RISE) RCB (GUARDRAIL)

This alternative uses the same structure as Alternate No. 1, but adds guardrail to both sides of SR 234 and shortens the structure length to 64-ft. The sideslope will be graded to a 2(H):1(V) to tie into the existing ground and will be protected by guardrail. The guardrail will be offset 4 ft from the travelway. Shoulders will be paved to front face of the guardrail. No Design Exception will be needed. Refer to the Typical Sections in Appendix F.

The total project limits will be approximately twice the length of the guardrail runout length of 185 ft for the installation of the guardrail. Therefore, the project limits will need to be approximately 188 feet on either side of the centerline of the structure (376' total). However, only approximately 20' of this will be full depth pavement replacement. The remainder of the project limits will be limited to HMA overlay and slope grading. The existing vertical profile provides adequate cover over the structure.

<u>ALTERNATE NO. 3 – 1.92' CIPP LINERS</u>

This alternative will rehabilitate the existing structure using a 1.92' diameter Cured-In-Place Pipe Liner, installation of a Class I Riprap apron for scour protection, and reconstruct the headwalls.

Since this alternate is considered a Partial 3R project, no other work will be required.

This alternate only addresses the condition of the structure and does not correct the hydraulic and safety deficiencies.

ALTERNATE NO. 4 – NO ACTION

If the structure remains in its existing state, the small structure will continue to deteriorate and could eventually fail creating unsafe roadway conditions and emergency repairs.

MAINTENANCE OF TRAFFIC CONCEPT

This project is not considered a mobility significant project per IDM Section 503-2.02. The following is the temporary traffic control plan concept that shall be used for the project:

A full closure of SR 234 with detour is anticipated for the project due to the type of work for Alternate Number 1 and 2. The proposed detour will utilize US 231, SR 236, and SR 75. The detour length is approximately 23.7 miles with 8.4 miles of additional travel. No local detour has been coordinated for this project. Due to the overall length of the detour and the rural setting, it is anticipated that locals will use county roads as a detour. An unofficial detour will be discussed with INDOT and the local agencies will be involved in the discussion regarding the potential damage to county roads due to the unofficial detour. Access to adjoining properties shall be maintained during construction.

For Alternate No. 3, only flagging operations will be required since all of the work will be off of the roadway.

ENVIRONMENTAL IMPACTS

Per the Indiana Geological & Water Survey, wetlands are not present near the structure. The stream is possibly considered Waters of the U.S. The stream does show up as a blue line on the latest USGS Quad Map.

The total impacts to the stream are anticipated to remain under the 300-foot threshold for both alternates. Therefore, if the stream is determined to be a Waters of the U.S. by the U.S. Army Corps of Engineers, the IDEM 401 and USACE 404 permits will not need to be elevated from the anticipated regional general permits to individual permits.

A Categorical Exclusion (CE) Level 1 was originally anticipated for this project. A CE Level 2 is anticipated for Alternate No. 1 and 2 since 0.5 acres of right of way is anticipated.

PERMITS REQUIRED

There are two anticipated permits required. The USACE 404 – Regional General Permit and the IDEM 401 – Regional General Permit are anticipated. An IDEM Rule 5 Application may be required if the limits of disturbance exceed one acre in the final design. No other permits are anticipated for the project.

RIGHT-OF-WAY IMPACTS

Per the as-built plans, the existing apparent right of way is a constant 30' offset from the roadway centerline to the north and a constant 40' offset from the roadway centerline to the south within the project limits. Parcel data indicates that the southern right of way was a land grant.

However, for this project the existing right of way is assumed to be taken at the existing edge of pavement since the parcel documentation shows that the land grants were not filed in a timely manner (approximately 25 years later).

It is anticipated that approximately 0.5 acres of right of way will be reacquired for this project. Of the right of way being acquired, approximately 0.45 acres will be requiring apparent right of way.

Alternate No.	Apparent Right of Way Reacquisition	Permanent Right of Way Acquisition	Temporary Right of Way Acquisition		
1	0.45	0.05	0.00		
2	0.45	0.05	0.00		
3	0.11	0.00	0.17		

Table 4: Right of Way

RAILROAD IMPACTS

There are no railroads in the vicinity of the project, so there are no anticipated impacts to railroads.

UTILITY IMPACTS

Per an 811 Design Ticket, there are two utilities within the area: AT&T - Distribution and Hendricks Power Cooperative. During the site visit, overhead utilities are observed on the north side of the road. The poles are approximately 28 feet off of the existing edge of pavement. Permanent impact or relocation of the overhead utility north of the roadway are subject to final design and the alternate chosen.

The proposed construction may have a temporary impact on the overhead facilities. The crane required for installation may be too close to the overhead lines and would have a high probability of arcing. The overhead electric lines will likely need to be de-energized while the culvert is installed.

SURVEY REQUIREMENTS

The survey requirements include the culvert inlets, edge of roadway, existing headwalls, and topographic features.

INITIAL FIELD CHECK MEETING

The initial field check meeting was held at the project site on July 19, 2019. The meeting minutes can be found in Appendix H.

PRELIMINARY COST ESTIMATE

The preliminary construction cost estimate for each of the alternatives can be found in Table 3. See Appendix F for the quantity calculations, full cost estimate, and the Life Cycle Cost Analysis.

The life cycle cost analysis only includes the cost of guardrail replacement due to damage or safety upgrades. The life cycle cost analysis does not include the pavement resurfacing, pavement replacement, pavement markings, or any other incidentals that would be considered similar for all options. The life of Alternate No. 1 and 2 is 75 years and the life of Alternate No. 3 is 50 years. At 50 years for Alternate No.3, the structure will have to be replaced.

Alternate No.	Alternative Description	Preliminary Cost Estimate	Preliminary R/W Costs	Life Cycle Additional Costs	Total Initial Cost	Total Life Time Costs
1	Reinforced Concrete Box	\$245,000	\$5,000	\$0	\$225,000	\$225,000
2	Reinforced Concrete Box with guardrail	\$316,000	\$5,000	\$73,000	\$297,000	\$365,000
3	CIPP Liner	\$99,000	\$2,800	\$0	\$101,800	\$101,800

Table 5: Preliminary Cost Estimates for the Alternatives

Based on the initial investment at construction and when the Total Life Time Cost are accounted for, Alternate No. 3 is least expensive though it has a shorter design life than the other alternates.

The recommended alternate is Alternate No. 1, the Reinforced Concrete Box without guardrail since this alternate provides the lowest cost in a 75 year period.

PHASE COSTS FOR CN/PE/RR/RW/UT

The current SPMS indicates \$120,000 for PE, \$10,000 for RW, and \$223,561 for CN. The recommended alternate is below the programmed cost in the SPMS.

CONCURRENCE

[Title

This document was prepared	d by:		
	7	_[Date]	04/27/2020
Nicholas Bergman, P.E.			
Project Manager – Infrastruc	ture Engineering, Inc		
Reviewed by: Asset Engineer Review Chris Wheeler, P.E.	5/1/2020	15	
[Name] [Title]	0/1/2020	_[Date]	
Reviewed by: Scope Manager Review Michael L E	ibank	[Date]	5/6/2020
[Name] Mike Eubank [Title] District Scoping			
Reviewed by: District Traffic Engineer Systems (1)	stem Asset Mana	ger	
Scott J. Chandler	<u>r</u>	_[Date]	
[Name]	5-6-2020		

APPENDIX E – INDOT HYDRAULICS APPROVAL LETTERS

March 20, 2020

TO: Tamara Montgomery


INDOT Project Manager


FROM: Meagan Froman, E.I.T.

Hydraulics Engineer

THROUGH: Merril Dougherty, P.E.

Hydraulics Engineer





SUBJECT: Hydraulic Review

Des. #: 1800155

Asset Name: CV 234-054-46.50

County: Montgomery

Location: 6.55 miles W of SR 75
Crossing: UNT to Little Raccoon Creek
DNR CIF Permit Required (Y/N): No
Legal Drain (Y/N): No

Site Parameters					
Drainage Area	123.98	acres			
Q ₁₀₀ Discharge	167.78	cfs			
Q ₂₅ Discharge	132.16	cfs			
Q ₁₀₀ Water Surface Elevation	97.49	ft.			
Design Roadway Serviceability Elevation	100.00	ft.			

Parameter	Existi	ing	Proposal 1		Proposal 2	
Stanistina Sira & Trus	Triple 2	2' ID	Triple 1.92' ID		8' x 4' RCB	
Structure Size & Type	CMP's		CIPP Liners		with 18" Sump	
Q ₁₀₀ Headwater Elevation	100.59	ft.	100.58	ft.	100.31	ft.
Q ₂₅ Headwater Elevation	100.50	ft.	100.48	ft.	99.83	ft.
Meets Roadway Serviceability @ Q ₂₅ (Y/N)	No		No		Yes	
Backwater	3.10	ft.	3.09	ft.	2.82	ft.
Assumed Flowline Elevation	95.79 ft.					
Sump Depth	0	in.	0	in.	18	in.

ID = inside pipe diameter



Existing Conditions and Analysis

The existing structure is approximately 48' long and has a mostly rural watershed of crops with pavement and small residential and industrial areas. Flow through the structure runs north to south, and the downstream channel consists of crops.

Hydrology was performed using the Rational Method, and hydraulic analysis was performed with HY-8 Version 7.2. The tailwater elevation was determined using LiDAR data, and the cross-section was located about 100' downstream of the existing culvert. The elevations in the table are based on the downstream existing invert and proposed flowline elevation of 95.79 ft. This datum was determined from using field survey and should only be used for hydraulic purposes. The Q_{100} water surface elevation is based on the existing outlet depth.

Review of Proposals

Liners proposals:

Proposal 1: 1.92' ID CIPP Liners

Replacement proposals:

Proposal 2: 8' x 4' RCB with 18" Sump

This replacement proposal may require a grade raise; the designer should ensure cover requirements are met.

Riprap Design Recommendations

Parameter	Proposal 1		Proposal 2		
Q ₂₅ Outlet Velocity	8.75	ft/s	8.46	ft/s	
Minimal Outlet Riprap Size	Class 1		Class 1		
Inlet Riprap Needed (Y/N)	No		Ye	Yes	
Q ₂₅ Natural Channel Velocity	2.07 ft/s				
Minimal Inlet Riprap Size	Revetment				

Class 1 riprap on geotextiles should be used at the outlet and placed according to IDM Figure 203-2J regardless of which proposal is selected. Revetment riprap should also be placed at the inlet according to IDM Figure 203-2J if Proposal 2 is selected. There was no evidence of scour observed at the inlet during the site visit, but if Proposal 1 is selected and the designer determines a need for inlet protection, revetment riprap or larger may be used.

Alternative scour protection designs should be submitted to the INDOT Office of Hydraulics for review and approval.

If you have any questions or comments, please contact me at (317) 233-7755 or MFroman@indot.IN.gov.



Culvert Inspection Report

CV 234-054-46.50 SR 234 over



Inspection Date: 05/12/2020

Inspected By: Daniel W. Bewley

Inspection Type(s): Culvert


TABLE OF CONTENTS

	PAGE NUMBER
REPORT COVER	3
LOCATION MAP	4
EXECUTIVE SUMMARY	5
CULVERT INSPECTION OUTPUT REPORT	6
PICTURES	8

Inspector: Daniel W. Bewley Asset Name: CV 234-054-46.50

Inspection Date: 05/12/2020 Facility Carried: SR 234

Culvert Inspection Report



Latitude: 39.91573 Longitude: -86.75280 Inspector: Daniel W. Bewley Structure Number: 93000817
Inspection Date: 05/12/2020 Facility Carried: SR 234

Culvert Inspection Report

Executive Summary

5/12/2020. Culvert is in overall poor condition. SPMS shows Des# 1800155, Contract# R-41588, Letting Date 9/14/2022, Work Type Replacement & Project Status Active

The structure is in poor overall condition. This structure is programmed for replacement in 2020 (Matt Ference, 05-10-2019).

Structure Number: CV 234-054-46.50 Inspector: Bewley, Daniel

Large Culvert Inspection Report

93000817 (8) Asset Code: (27) Year Built: 0000

Asset Name: CV 234-054-46.50 (90) Inspection Date: 05/12/2020

OLD Culvert ID: 234-54-46.50 12 (91) Inspection Frequency: Team Assignment: 01 Additional Treatment Exists

Identification

01 (3) County Code: 054 (2) Highway Agency District:

Sub District: 1200 Ramp ID:

(42B) Type of Service (Under): 5 ■Adjacent to Roadway

(7) Facility Carried: SR 234 (6) Features Intersected:

6.55 W SR 75 (9) Location: (9.01) Location Additional Description:

(16) Latitude: 39.91573 (11) Milepoint: 46.50 (17) Longitude: -86.75280

Classification:

0 (26) Functional Classification of Inventory Route: 02 (104) Highway System of the Inventory Route:

Geometric Data

Culvert: Kind of Material: 3. Steel Culvert: Type of Structure: 3. Pipe Min Est Fill Cover (ft): 1.00

9.00 Culvert: Max. Vertical Opening (ft.): 02.00 Culvert: Max. Horizontal Opening (ft.): (34) Skew: 30

Original Culvert Shape: Round Barrel Length (ft.): 30.00

Measurement Remarks: From CV Chart

Structure Additional Corrugated Metal Pipe 2' x 2' Three pipes

Description:

Openings:

Opening Opening Opening Opening Direction Direction Latitude Longitude Latitude Longitude

1. 3. 2. 4.

Openings Comments:

☐ Follow Up Required:

**If checked, please Too small to enter. describe for follow up:

Endangered Species

Bats: seen or heard under structure? * Ν

Birds/swallows/nests seen? Empty nests present? Ν

* If yes, add one photo to the dropdown field

General Condition Ratings

(36A) Bridge Railings:	N	(36C) Approach Guardrail:	N
(36B) Transitions:	N	(36D) Approach Guardrail Ends:	N
Culvert:			
(62) Culvert - Rating:	4		
(62) Culvert Rating Comments:	exposed rebar at both	n throughout the structure. The head walls have sevends of the structure. All three pipes have rust hole aining their shape. No obvious changes since last in	s along the water line.
Deck:		,	•
(58) Deck:	N		
(58a) Deck Comments: Superstructure:			
(59) Superstructure:	N		
(59.01) Superstructure Comments:			
Substructure:			
(60) Substructure:	N		
(60.01) Substructure Comments:			
CV-Headwall/Anchor Rating	4		
CV-Wingwalls Rating	N		
Channel:			
(61) Channel and Channel Protection:	8		
(61.01) Channel and Channel Protection Comments:	The water flows from and does not have mu	the north to the south. The channel is an equalizer luch of a channel.	between two farm fields
Bank Erosion Rating:	7		
Drift/Sediment Rating	7		
Channel Alignment Rating	7		
	☐ Check ti	his box if culvert has OBSTRUCTED flow	
Describe Obstruction:			
Overtopping Frequency:	1		
Overtopping Frequency Comments:			

Inspector: Daniel W. Bewley Structure Number: 93000817
Inspection Date: 05/12/2020 Facility Carried: SR 234

Culvert Inspection Report

Pictures



PHOTO 1 Condition

Description Road alignment looking east



PHOTO 2 Condition

Description Road alignment looking west

Inspector: Daniel W. Bewley Structure Number: 93000817
Inspection Date: 05/12/2020 Facility Carried: SR 234

Culvert Inspection Report

Pictures



PHOTO 3 Condition

Description Pavement condition above culvert



PHOTO 4 Elevation, Condition

Description Profile looking North

Inspector: Daniel W. Bewley Structure Number: 93000817 Inspection Date: 05/12/2020

Facility Carried: SR 234

Culvert Inspection Report

Pictures



РНОТО 5 Elevation, Condition Description Profile looking south



РНОТО 6 Condition

Looking South through middle pipe showing no bottom Description

Inspector: Daniel W. Bewley Structure Number: 93000817 Inspection Date: 05/12/2020

Facility Carried: SR 234

Culvert Inspection Report

Pictures



РНОТО 7 Condition

Looking south through west pipe Description



РНОТО 8 Condition

Looking South through East pipe Description

Inspector: Daniel W. Bewley Structure Number: 93000817 Inspection Date: 05/12/2020 SR 234

Facility Carried:

Culvert Inspection Report

Pictures



РНОТО 9 Condition

Looking North through middle pipe showing rusted through areas Description



PHOTO 10 Condition

Looking North through West pipe Description

Inspector: Daniel W. Bewley Structure Number: 93000817 Inspection Date: 05/12/2020

Facility Carried: SR 234

Culvert Inspection Report

Pictures



PHOTO 11 Condition

Looking North through East pipe Description



PHOTO 12 Condition

Channel alignment on North side of road Description

Inspector: Daniel W. Bewley Structure Number: 93000817

Inspection Date: 05/12/2020 Facility Carried: SR 234

Culvert Inspection Report

Pictures



PHOTO 13 Condition

Description Channel alignment on South side of road